

PCN 客户确认通知单
PCN customer confirmation Notice

PCN NO#: 15123001

产品型号 Part No.	TYS3015xxx-1x;TYS4018xxx-1x; TYS5040xxx-1x;TYS6020xxx-1x; TYS6028xxx-1x;TYS6045xxx-1x; TYS8040xxx-1x; Where: 1x means, 10,11,12,13,14	提出日期 Submission date	2015-12-30																																																																						
		建议生效日期 Propose effective date	2016-03-01																																																																						
变更内容 Change content	Modify tooling to increase the solder pad area so as to be able mounted with higher stability.																																																																								
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4">Before change</th> </tr> <tr> <th>Series</th> <th>"C"</th> <th>"D"</th> <th>"E"</th> </tr> </thead> <tbody> <tr> <td>TYS3015</td> <td>1.5 max</td> <td>0.75±0.2</td> <td>1.50±0.2</td> </tr> <tr> <td>TYS4018</td> <td>1.8max</td> <td>0.95±0.2</td> <td>2.10±0.2</td> </tr> <tr> <td>TYS5040</td> <td>4.0 max</td> <td>1.25±0.2</td> <td>2.50±0.2</td> </tr> <tr> <td>TYS6020</td> <td>2.0 max</td> <td>1.55±0.3</td> <td>2.90±0.3</td> </tr> <tr> <td>TYS6028</td> <td>2.8 max</td> <td>1.55±0.3</td> <td>2.90±0.3</td> </tr> <tr> <td>TYS6045</td> <td>4.5 max</td> <td>1.55±0.3</td> <td>2.90±0.3</td> </tr> <tr> <td>TYS8040</td> <td>4.2 max</td> <td>2.00±0.3</td> <td>4.00±0.3</td> </tr> </tbody> </table>	Before change				Series	"C"	"D"	"E"	TYS3015	1.5 max	0.75±0.2	1.50±0.2	TYS4018	1.8max	0.95±0.2	2.10±0.2	TYS5040	4.0 max	1.25±0.2	2.50±0.2	TYS6020	2.0 max	1.55±0.3	2.90±0.3	TYS6028	2.8 max	1.55±0.3	2.90±0.3	TYS6045	4.5 max	1.55±0.3	2.90±0.3	TYS8040	4.2 max	2.00±0.3	4.00±0.3	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4">After change</th> </tr> <tr> <th>Series</th> <th>"C"</th> <th>"D"</th> <th>"E"</th> </tr> </thead> <tbody> <tr> <td>TYS3015</td> <td>1.5^{+0.2}_{-0.3}</td> <td>1.10±0.3</td> <td>0.80±0.3</td> </tr> <tr> <td>TYS4018</td> <td>1.8^{+0.2}_{-0.3}</td> <td>1.30±0.3</td> <td>1.40±0.3</td> </tr> <tr> <td>TYS5040</td> <td>4.0^{+0.2}_{-0.3}</td> <td>1.60±0.3</td> <td>1.80±0.3</td> </tr> <tr> <td>TYS6020</td> <td>2.0^{+0.2}_{-0.3}</td> <td>1.60±0.3</td> <td>2.80±0.3</td> </tr> <tr> <td>TYS6028</td> <td>2.8^{+0.2}_{-0.3}</td> <td>1.80±0.3</td> <td>2.40±0.3</td> </tr> <tr> <td>TYS6045</td> <td>4.5^{+0.2}_{-0.3}</td> <td>1.80±0.3</td> <td>2.40±0.3</td> </tr> <tr> <td>TYS8040</td> <td>4.0^{+0.2}_{-0.3}</td> <td>2.45±0.3</td> <td>3.10±0.3</td> </tr> </tbody> </table>	After change				Series	"C"	"D"	"E"	TYS3015	1.5 ^{+0.2} _{-0.3}	1.10±0.3	0.80±0.3	TYS4018	1.8 ^{+0.2} _{-0.3}	1.30±0.3	1.40±0.3	TYS5040	4.0 ^{+0.2} _{-0.3}	1.60±0.3	1.80±0.3	TYS6020	2.0 ^{+0.2} _{-0.3}	1.60±0.3	2.80±0.3	TYS6028	2.8 ^{+0.2} _{-0.3}	1.80±0.3	2.40±0.3	TYS6045	4.5 ^{+0.2} _{-0.3}	1.80±0.3	2.40±0.3	TYS8040	4.0 ^{+0.2} _{-0.3}	2.45±0.3
Before change																																																																									
Series	"C"	"D"	"E"																																																																						
TYS3015	1.5 max	0.75±0.2	1.50±0.2																																																																						
TYS4018	1.8max	0.95±0.2	2.10±0.2																																																																						
TYS5040	4.0 max	1.25±0.2	2.50±0.2																																																																						
TYS6020	2.0 max	1.55±0.3	2.90±0.3																																																																						
TYS6028	2.8 max	1.55±0.3	2.90±0.3																																																																						
TYS6045	4.5 max	1.55±0.3	2.90±0.3																																																																						
TYS8040	4.2 max	2.00±0.3	4.00±0.3																																																																						
After change																																																																									
Series	"C"	"D"	"E"																																																																						
TYS3015	1.5 ^{+0.2} _{-0.3}	1.10±0.3	0.80±0.3																																																																						
TYS4018	1.8 ^{+0.2} _{-0.3}	1.30±0.3	1.40±0.3																																																																						
TYS5040	4.0 ^{+0.2} _{-0.3}	1.60±0.3	1.80±0.3																																																																						
TYS6020	2.0 ^{+0.2} _{-0.3}	1.60±0.3	2.80±0.3																																																																						
TYS6028	2.8 ^{+0.2} _{-0.3}	1.80±0.3	2.40±0.3																																																																						
TYS6045	4.5 ^{+0.2} _{-0.3}	1.80±0.3	2.40±0.3																																																																						
TYS8040	4.0 ^{+0.2} _{-0.3}	2.45±0.3	3.10±0.3																																																																						
变更类型 Change type	<input checked="" type="checkbox"/> 规格变更 SPEC change <input type="checkbox"/> 生产方法变更 method change <input type="checkbox"/> 生产机器变更 machine change <input type="checkbox"/> 包装方法变更 package change <input type="checkbox"/> 生产环境或生产地点变更 Environment or production location change																																																																								
变更前后数据对比 Before change contrast after change																																																																									
比对项目 Contrast items	变更前 Before change	变更后 After change																																																																							
品质数据 Quality data	Pass	Pass																																																																							
有害物质含量测试 HS test	pass	pass																																																																							

PCN 客户确认通知单
PCN customer confirmation Notice

PCN NO#: 15123001

结论 Conclusion	Suggest to change the dimensions "C," "D," "E".
------------------	---

QA: *Jan 2016. 1. K*

ENG: *12.30*

客户意见 Customer advice	<input type="checkbox"/> 同意 agree	<input type="checkbox"/> 不同意 disagree
	Advice:	
	客户签名 customer signature:	日期 Date: