


# SKINTOP® SLM/SLRM

## Strain relief with metric thread



SKINTOP® SLM/SLRM is a durable, liquid-tight, easy-to-assemble strain relief cable gland with metric thread that is universally suited for all types of machinery & equipment, including automation, motion control, process control, and robotics. SKINTOP® SLRM includes reducer bushing.

### Application advantage

- The heavy duty SKINTOP® design provides great pullout strength and very reliable strain relief
- Superior integrated locking mechanism includes an internal ratchet for vibration-proof protection
- Multi-trapezoidal thread requires just one twist to tighten
- Generous high-quality neoprene bushing provides a liquid-tight and dust-proof hermetic seal

### Approvals



### Technical data

<b>Material:</b>		<b>Temperature range:</b>	
- body:	polyamide	- static:	-40°C to +100°C
- bushing:	CR	- dynamic:	-20°C to +100°C
<b>Color:</b>	black (RAL 9005), UV resistant gray (RAL 7001)	<b>IP Protection:</b>	70 PSI
		- seal:	IP68, 5 bar IP69 NEMA 1, 12
<b>Locknuts:</b>	included		

Part number with locknut		Part number without locknut*		Thread	UL status	Clamping range (øF)		Wrenching flats (SW)	Overall length (C)	Thread length (D)	Pack size
black	gray	black	gray			in	mm				
<b>Standard</b>											
S2507	S1507	53111200	53111000	M12 x 1.5	Recognized	0.138 - 0.276	3.5 - 7	0.591	1.181	0.315	100
S2509	S1509	53111210	53111010	M16 x 1.5**	Recognized	0.157 - 0.394	4 - 10	0.748	1.339	0.315	100
S2513	S1513	53111220	53111020	M20 x 1.5**	Listed	0.236 - 0.512	6 - 13	0.984	1.457	0.354	100
S2516	S1516	53111230	53111030	M25 x 1.5**	Listed	0.315 - 0.669	8 - 17	1.181	1.575	0.394	50
S2521	S1521	53111240	53111040	M32 x 1.5	Listed	0.354 - 0.827	9 - 21	1.417	1.850	0.394	25
S2529	S1529	53111250	53111050	M40 x 1.5	Listed	0.630 - 1.102	16 - 28	1.811	2.047	0.394	10
S2536	S1536	53111260	53111060	M50 x 1.5	Listed	1.063 - 1.339	27 - 34	2.165	2.441	0.472	5
S2542	S1542	53111270	53111070	M63 x 1.5	Listed	1.339 - 1.772	34 - 45	2.598	2.795	0.472	5
<b>Reducer bushing</b>											
S2607	S1607	53111300	53111100	M12 x 1.5	Recognized	0.079 - 0.197	2 - 5	0.591	1.181	0.315	100
S2609	S1609	53111310	53111110	M16 x 1.5**	Recognized	0.138 - 0.276	3.5 - 7	0.748	1.339	0.315	100
S2613	S1613	53111320	53111120	M20 x 1.5**	Listed	0.157 - 0.394	4 - 10	0.984	1.457	0.354	100
S2616	S1616	53111330	53111130	M25 x 1.5**	Listed	0.197 - 0.512	5 - 13	1.181	1.575	0.394	50
S2621	S1621	53111340	53111140	M32 x 1.5	Listed	0.236 - 0.591	6 - 15	1.417	1.850	0.394	25
S2629	S1629	53111350	53111150	M40 x 1.5	Listed	0.354 - 0.906	9 - 23	1.811	2.047	0.394	10
S2636	S1636	53111360	53111160	M50 x 1.5	Listed	0.945 - 1.142	24 - 29	2.165	2.441	0.472	5
S2642	S1642	53111370	53111170	M63 x 1.5	Listed	1.102 - 1.535	28 - 39	2.598	2.795	0.472	5

\* The use of a locknut is required per UL if the end-use application consists of inserting the cable gland through a non-threaded hole

\*\* Metric sizes M16, M20, and M25 also available in an extended thread version. To maintain UL rating, please use a locknut

Orders of 2000 pieces or more per item will be bulk packaged unless otherwise requested