

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t1619ems8#trpbf

(Engineering Calculation)

MSOP

(printed on: 2020-07-11 20:13:22)

**TOTAL MASS (g) : 0.027658**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.002301	1000000	83194.65625		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.010433	975000	377214.15625		
		Iron (Fe)	7439-89-6	0.000257	24000	9292.05859375		
		Phosphorus (P)	7723-14-0	0.000003	300	108.46761322		
		Zinc (Zn)	7440-66-6	0.000007	700	253.091094971		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.010700</b>	<b>1000000</b>	<b>386867.8125</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000710	1000000	25671.5703125		
		<b>External Plating Total:</b>				<b>0.000710</b>	<b>1000000</b>	<b>25671.5703125</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000086	1000000	3109.40478516		
<b>Internal Plating Total:</b>				<b>0.000086</b>	<b>1000000</b>	<b>3109.40478516</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000758	750000	27406.1484375		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000253	250000	9147.43554688		
<b>Die Attach Total:</b>				<b>0.001011</b>	<b>1000000</b>	<b>36553.5859375</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.001659	130000	59982.5859375		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.010591	830000	382926.8125		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000447	35000	16161.6728516		
		Carbon Black (C)	1333-86-4	0.000064	5000	2313.97583008		
		<b>Encapsulation Total:</b>				<b>0.012761</b>	<b>1000000</b>	<b>461385.03125</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000089	1000000	3217.87255859		
					<b>TOTAL MASS (g) :</b>	<b>0.027658</b>		