

ITS4060S-SJ-N**Smart Power high-side switch for industrial applications****Reference: Data Sheet Rev. 1.0****Overview**

This document lists the errata of the ITS4060S-SJ-N related to the Data Sheet, Rev. 1.0 (2012-09-01).

The ESD ratings for HBM listed in the data sheet according to standard EIA/JESD 22-A 114 do partly differ from allowable ratings of the device for ESD HBM derived from measurement results according to standard ANSI/ESDA/JEDEC JS001 (1.5 k Ω , 100 pF).

Neither the hardware/silicon of the listed product itself nor the physical properties or the robustness with respect to ESD have changed or were modified.

Affected Products:

- ITS4060S-SJ-N

Description

1 Description

1.1 ESD ratings for Human Body Model (HBM)

The ESD ratings for HBM robustness listed in the data sheet according to standard EIA/JESD 22-A 114 do partly differ from allowable ratings of the device for ESD HBM derived from recent measurements according to standard ANSI/ESDA/JEDEC JS001 (1.5 kΩ, 100 pF).

Neither the hardware/silicon nor the ESD robustness of the product itself have changed.

Table 1 shows the existing discrepancies between the ESD robustness as listed in the datasheet Rev 1.0 and the results of remeasurements according ANSI/ESDA/JEDEC JS001.

Table 1

Parameter	Symbol	Values			Unit	Note or Test Condition
		Min.	Typ.	Max.		
ESD Susceptibility for HBM as listed in data sheet Rev. 1.0 according EIA/JESD 22-A 114						
ESD susceptibility (input pin IN)	V_{ESD}	-1	-	1	kV	HBM listed in data sheet Rev. 1.0 according EIA/JESD 22-A 114
ESD susceptibility (all other pins)	V_{ESD}	-5	-	5	kV	HBM listed in data sheet Rev. 1.0 according EIA/JESD 22-A 114

Maximum allowable ESD Susceptibility for HBM derived from measurements according ANSI/ESDA/JEDEC JS001 (1.5 kΩ, 100 pF)

ESD susceptibility (input pin IN)	V_{ESD}	-1	-	1	kV	HBM ratings derived from measurements according to ANSI/ESDA/JEDEC JS001 (1.5 kΩ, 100 pF)
ESD susceptibility (output pin OUT)	V_{ESD}	-6	-	6	kV	HBM ratings derived from measurements according to ANSI/ESDA/JEDEC JS001 (1.5 kΩ, 100 pF)
ESD susceptibility (all other pins)	V_{ESD}	-4	-	4	kV	HBM ratings derived from measurements according to ANSI/ESDA/JEDEC JS001 (1.5 kΩ, 100 pF)

Planned Fixes

Update of data sheet: The data sheet will be updated to Rev. 1.1 which will reflect ESD ratings for HBM according to ANSI/ESDA/JEDEC JS001 results.

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2019-07-18
Published by
Infineon Technologies AG
81726 Munich, Germany

© 2019 Infineon Technologies AG.
All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com
Z8F66302201

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.